

HighPoint Rocket 7604A Compatibility List

2025/4/17

This document was designed to serve as general reference for compatibility between the HighPoint Rocket 7604A NVMe RAID AIC and specific motherboards/SSDs described herein.

The motherboards included in this document are recommended for HighPoint Rocket 7604A x16 PCIe 5.0 configurations. Specific motherboards may have special requirements or restrictions. Please refer to the motherboard's PCIe Expansion slot settings.

Note: *Bifurcation is not required. HighPoint Rocket 7604A NVMe RAID AIC can be used with "Non-Bifurcation" motherboards.*

Motherboard Compatibility List

Note: The recommended PCIe slot we filled in are based on the description of the motherboard manual.

Manufacture	Product Name	Chipset/CPU Mode	Recommended PCIe slot #	Data RAID support	Boot RAID support
ASRock	Z790 PG Lightning- PCIe5.0	Intel Z790	PCIe1	√	√
ASRock	ROMED8-2T	AMD EPYC 7002/7003 Series	PCIe1, PCIe2, PCIe3, PCIe4, PCIe5, PCIe6, PCIe7	√	√
ASRock	WRX90 WS EVO	AMD WRX90	PCIe1 PCIe2 PCIe3 PCIe4 PCIe5 PCIe7	√	√
ASUS	Pro WS WRX80E-SAGE SE WIFI	AMD WRX80	PCIe4.0/3.0 X16_1 PCIe4.0/3.0 X16_2 PCIe4.0/3.0 X16_3 PCIe4.0/3.0 X16_4 PCIe4.0/3.0 X16_5 PCIe4.0/3.0 X16_6 PCIe4.0/3.0 X16_7	√	√
ASUS	PRO WS WRX90E-SAGE SE	AMD WRX90	PCIEX16(G5)_1 PCIEX16(G5)_2 PCIEX16(G5)_3 PCIEX16(G5)_4 PCIEX16(G5)_5 PCIEX16(G5)_6 PCIEX16(G5)_7	√	√
ASUS	PRIME X670-P WIFI	AMD X670	PCIEX16_1(gen5)	√	√
ASUS	ASUS ProArt X670E-CREATOR WIFI	AMD X670	PXIEX16_1, PCIEX16_2, PCIEX16_3	√	√
ASUS	Pro WS TRX50-SAGE WIFI	AMD TRX50	PCIEX16(G5)_1 PCIEX16(G5)_2 PCIEX16(G4)_2	√	√
ASUS	MAXIMUS Z790 DARK HERO	Intel Z790	PCIEX16(G5)_1	√	√
ASUS	Pro WS W790E-SAGE SE	Intel W790	PCIe X16(G5)_1 PCIe X16(G5)_2 PCIe X16(G5)_3 PCIe X16(G5)_4 PCIe X16(G5)_5 PCIe X16(G5)_7	√	√
ASUS	Prime X870-P WiFi	AMD X870	PCIEX16(G5)	√	√
Dell	Precision 7960 Tower Workstation	Intel W790	SLOT1 PCIe5 x16 SLOT4 PCIe4 x16 SLOT5 PCIe5 x16 SLOT8 PCIe4 x16	√	√
GIGABYTE	Z790M AORUS ELITE AX	Intel Z790	PCIEX16	√	√
HP	Z6 G5 A	AMD Pro 695	SLOT 1:PCIe Gen5 x16 SLOT 2:PCIe Gen5 x16 SLOT 4:PCIe Gen5 x16 SLOT 5:PCIe Gen5 x16 SLOT 6:PCIe Gen5 x16	√	√
Supermicro	X12DPi-N6	Intel C621A	CPU1 SLOT2 PCI-E 4.0 x16 CPU1 SLOT3 PCI-E 4.0 x16 CPU2 SLOT4 PCI-E 4.0 x16 CPU2 SLOT5 PCI-E 4.0 x16	√	√
Supermicro	X12DPi-NT6	Intel C621A	CPU1 SLOT2 PCI-E 4.0 x16 CPU1 SLOT3 PCI-E 4.0 x16 CPU2 SLOT4 PCI-E 4.0 x16 CPU2 SLOT5 PCI-E 4.0 x16	√	√
Supermicro	X12DPL-i6	Intel C621A	CPU2 SLOT1 PCI-E 4.0 x16 CPU1 SLOT2 PCI-E 4.0 x16 CPU1 SLOT3 PCI-E 4.0 x16 CPU1 SLOT4 PCI-E 4.0 x16	√	√
Supermicro	X12DPL-NT6	Intel C621A	CPU2 SLOT1 PCI-E 4.0 x16 CPU1 SLOT2 PCI-E 4.0 x16	√	√

			CPU1 SLOT3 PCI-E 4.0 x16 CPU1 SLOT4 PCI-E 4.0 x16		
Supermicro	X12DAI-N6	Intel C621A	CPU1 SLOT1 PCI-E 4.0 x16 CPU2 SLOT2 PCI-E 4.0 x16 CPU1 SLOT3 PCI-E 4.0 x16 CPU2 SLOT4 PCI-E 4.0 x16 CPU1 SLOT5 PCI-E 4.0 x16	√	√
Supermicro	X12-SPL-F	Intel C621A	CPU1 SLOT6 PCI-E 4.0 x16	√	√
Supermicro	H12SSL-i	AMD EPYC 7002/7003 Series	CPU SLOT1 PCI-E 4.0 X16 CPU SLOT3 PCI-E 4.0 X16 CPU SLOT5 PCI-E 4.0 X16 CPU SLOT6 PCI-E 4.0 X16 CPU SLOT7 PCI-E 4.0 X16	√	√
Supermicro	H12DSG-O	AMD EPYC 7002/7003 Series	1X PCIE4.0 X16 via Riser slot	√	√
Supermicro	H12DSi-NT6	AMD EPYC 7002/7003 Series	CPU SLOT2 PCI-E 4.0 x16 CPU SLOT4 PCI-E 4.0 x16 CPU SLOT6 PCI-E 4.0 x16	√	√
Supermicro	H12DSU-iN	AMD EPYC 7002/7003 Series	1X PCIE4.0 X16 via Riser slot 1X PCIE4.0 X32 via Riser slot	√	√
Supermicro	H12SSW-NT	AMD EPYC 7002/7003 Series	1X PCIE4.0 X16 via Riser slot 1X PCIE4.0 X32 via Riser slot	√	√
Supermicro	H12SSL-NT	AMD EPYC 7002/7003 Series	CPU SLOT1 PCI-E 4.0 X16 CPU SLOT3 PCI-E 4.0 X16 CPU SLOT5 PCI-E 4.0 X16 CPU SLOT6 PCI-E 4.0 X16 CPU SLOT7 PCI-E 4.0 X16	√	√
Supermicro	H12SSL-C	AMD EPYC 7002/7003 Series	CPU SLOT1 PCI-E 4.0 X16 CPU SLOT3 PCI-E 4.0 X16 CPU SLOT5 PCI-E 4.0 X16 CPU SLOT6 PCI-E 4.0 X16 CPU SLOT7 PCI-E 4.0 X16	√	√
Supermicro	H12SSL-CT	AMD EPYC 7002/7003 Series	CPU SLOT1 PCI-E 4.0 X16 CPU SLOT3 PCI-E 4.0 X16 CPU SLOT5 PCI-E 4.0 X16 CPU SLOT6 PCI-E 4.0 X16 CPU SLOT7 PCI-E 4.0 X16	√	√
Supermicro	SYS-2025HS-TNR	AMD EPYC 9004 Series	SLOT1, SLOT3, SLOT5, SLOT7	√	√
Supermicro	H13DSH	AMD EPYC 9004 Series	JPCIE1 x16, JPCIE2 x16	√	√
Supermicro	SYS-741GE-TNRT	Intel C741	P1 SLOT2, P1 SLOT4, P2 SLOTS5, P2 SLOT7, P2 SLOT9, P2 SLOT10 P2 SLOT11	√	√
Supermicro	X13SEI-TF	Intel C741	CPU SLOT4 PCIe 5.0 x16 CPU SLOT6 PCIe 5.0 x16	√	√

NVMe SSD Compatibility List

Manufacture	Model/Series	Form Factor	Capacity	Remark
PCIe Gen4				
Samsung	980PRO	M.2 2280	250GB, 500GB, 1TB, 2TB	
Samsung	990PRO	M.2 2280	1TB, 2TB, 4TB	
Samsung	990EVO	M.2 2280	1TB, 2TB	
Seagate	FireCuda 530	M.2 2280	500GB, 1TB, 2TB, 4TB	
Sabrent	Rocket NVMe 4.0	M.2 2280	500GB, 1TB, 2TB	
Sabrent	Rocket 4 Plus	M.2 2280	500GB,1TB, 2TB, 4TB, 8TB	
KIOXIA	XG8 Series	M.2 2280	512GB, 1024GB, 2048GB, 4096GB	
Phison	PS5018-E18	M.2 2280 Double Side	2000GB,2048GB,4000GB,4096GB,8000GB,8192GB	
Phison	PS5027-E27T	M.2 2280	512GB, 500GB, 1024GB, 1000GB, 2048GB, 2000 GB	
Western Digital	SN850X	M.2 2280	1TB, 2TB, 4TB, 8TB	
PCIe Gen5				
Crucial	Crucial T700	M.2 2280	1TB, 2TB, 4TB	
Crucial	Crucial T705	M.2 2280	1TB, 2TB, 4TB	
Phison	PS5026-E26 Gen5 Pro	M.2 2280	1000GB, 2000GB, 4000GB	
Phison	PS5031-E31T	M.2 2280	1TB-8TB	

If you have any questions about compatibility, please contact us at Sales@highpoint-tech.com