

# RocketStor 6418TS

## 8-Bay Q-SATA Turbo RAID Tower Enclosure



- Dual SFF-8088 Ports
- Robust Turbo RAID Architecture intelligently utilizes system resource to accelerate RAID 0 Performance up to 3,000MB/s
- 8x Hot-swappable HDD / SSD Drive Bays
- Up to Eight 8TB SATA HDDs and SSDs, up to 64TB Storage Capacity
- RAID 0, 1, 5, 6, 10, 50 & JBOD
- Industry Most Cost-effective SATA RAID 6 Storage solution
- User Friendly RAID Management Suite
- Windows, Linux, FreeBSD and Mac compatible

### Industry's Lowest-Cost 8-Bay RAID 5 & 6 Enclosure

The RocketStor 6418TS utilizes 2 of HighPoint's Q-SATA connectivity ports to directly support up to 8 SATA hard drives or SSD's in one or more RAID Storage configurations. The dual Q-SATA connectivity solution merges as the performance capabilities of eight independent 6Gb/s SATA channels into a single, super-speed connectivity solution that is capable of performing up to 2x 2,400MB/s. It is an ideal RAID storage solution for performance hungry workstations.



**Q-SATA Connectivity Solution:** **Q-SATA**, or **Quad-SATA** is a connectivity Solution that utilizes SFF-8088 connectors to deliver true SATA 6Gb/s RAID Storage performance at an affordable price point. "Q" refers to the performance capability of the connection, which quadruples the SATA transfer bandwidth up to 2x 2,400MB/s, and fully optimizes RAID performance for up to 8 SATA 6Gb/s SSD or hard drives. Q-SATA features a robust locking mechanism to ensure stable and reliable storage connectivity.

**Industry's Most Affordable RAID 6 Storage Solution:** The majority of today's PC platforms benefit from efficient, high-performance processors and abundant cost-effective memory. The RocketStor 6418TS Turbo RAID solution was designed to intelligently utilize these surplus system resources to accelerate or maximize the transfer performance potential of RAID storage applications. RocketStor Turbo Class solutions offer exceptional RAID level support including RAID 0, 1, 5, 6, 10, 50 & JBOD.




**Robust Redundant RAID 5 & 6 Protection:** The RocketStor 6418TS has integrated a series of preemptive security measures to maximize Storage uptime whenever data is needed. Redundant RAID 5 and 6 protection shields storage configurations from 1 or 2 disk failures without compromising data accessibility.

**Robust RAID Recovery:** Built-in NVRAM constantly tracks in-progress writes to preserve the integrity of data in the event of a drive failure or system crash, and streamline recovery procedures while minimizing downtime. Administrators can initialize or schedule RAID verification sessions that check each disk member of an array for parity consistency. If any parity related problems are found, the interface will immediately rebuild the array to ensure the integrity of your data.



**Open-Box Storage Solution:** The RocketStor 6418TS features an "open-box" approach to storage, which grants customers the freedom to use their choice of SAS or SATA drive from all major drive brands including HGST, Seagate, Toshiba and WDC. Customers can add drives as needed to meet the evolving performance or capacity requirements of the storage application. The eight removable hot-swap bays support any 2.5" or 3.5" SATA Hard Drive or SSD, and up to 64TB of total storage capacity. Enterprise /NAS class drives are recommended for the RocketStor 6418TS; customers can tailor storage configurations to meet each application's performance and budget requirements.







**Simple and Easy Storage Expansion:** Online Capacity Expansion and RAID Migration allow customers to modify RAID configurations or expand existing storage while avoiding complicated, time consuming backup and restoration procedures.

**Intelligent Storage Management Solution:** The RocketStor 6418TS includes a user-friendly web-based management interface available for Windows, and Mac OSX operating systems. Novices and experts alike, can quickly and easily configure, monitor, maintain and troubleshoot RAID configurations and individual storage devices, all from a single, unified software suite. Advanced Management Features allow customers to configure Email notification to inform one or more users of changing storage conditions while outside of the work environment, and manage storage remotely via a local network connection.



<b>Port Type</b>	SFF-8088 (Q-SATA)
<b>Number of Ports</b>	2x SFF-8088 (Q-SATA)
<b>Optional Battery Backup Module (HPTBBU-05)</b>	N/A
<b>Bus Interface</b>	PCIe 2.0 x8
<b>RAID Level</b>	0, 1, 5, 6, 10, 50 and JBOD (RAID 6 support limited to PC platforms)
<b>Operating System</b>	Window Server 2008 and Window 7 and later
	Linux: RedHat Enterprise, Open SuSE, Fedora Core, Debian, Ubuntu
	FreeBSD
	Driver embedded into FreeBSD 9.0 and later
	Mac OS X 10.6 and later
	Driver embedded into Mac OS X 10.10 and later
<b>Max. Capacity</b>	up to 64 TB
<b>Number Of drives</b>	Up to 8
<b>Drive Interface</b>	SATA
<b>Drive Form Factor</b>	2.5", 3.5"
<b>Material</b>	Brushed aluminum housing
<b>Enclosure Dimension</b>	13.00"(H)x 5.67"(W)x10.12"(D)
<b>Enclosure Weight</b>	13.40 lbs.
<b>Warranty</b>	1 Year
<b>Advanced RAID Features</b>	Storage Health Inspector
	Redundant RAID Configurations
	Multiple RAID Partitions supported
	Online Array Roaming
	Online RAID Level Migration (ORLM)
	Online Capacity Expansion (OCE)
	RAID Initialization Background/Foreground/Quick
	Global Hot Spare Disk support
	Automatic and configurable RAID Rebuilding Priority
	Disk Format compatible: 512, 512e, 4Kn
	Larger than 2 TB Drive and RAID Array support
	Native Command Queuing
	Write Back and Write Through

<b>Storage Monitoring and Management Suite</b>	
<b>RAID Management Suites</b>	Browser-Based management tool
<b>Password Secured RAID management Suites</b>	Default no password needed to access WebGUI in Mac
<b>LED Indicator</b>	Power, Present, Active, Fail, Rebuilding and Identify
<b>SMTP Email Alert Notification</b>	Email Alert Notification
<b>Power Supply</b>	AC INPUT: 100-240V ~ 5A 50/60Hz; DC OUTPUT: 250W
<b>Internal Fan</b>	80x80x25mm, Dual Fan
<b>Alarm Buzzer</b>	Buzzer beeping when failed drive or array occurs
<b>Operating Environment</b>	
<b>Temperature</b>	(operating) 5°C – 45°C / (non-operating) -40°C – 65°C
<b>Relative Humidity</b>	(operating) 8% – 90% RH (Non-condensing) / (non-operating) 5% – 95% RH (Non-condensing)
<b>Kit Contents</b>	
<b>Kit Contents</b>	1x 8-Bay Tower Enclosure
	1x 8-Port SATA 6Gb/s Turbo RAID PCIe2.0 x8 Host Adapter
	1x Low-Profile Bracket
	8x Drive Trays
	1x UL Power Cord
	32x 3.5" HDD mounting screws
	32x 2.5" SSD mounting screws
1x Quick Installation Guide	
<b>Optional Accessories</b>	
	<p><b>RocketStor TRAY-T</b> - Removable hot-swap drive tray</p> <p><b>Key Feature:</b> 2.5" and 3.5" drive compatible</p> <p>The RocketStor RSTRAY-T is a Drive Tray for HighPoint RocketStor 6314A, 6318A, 6414S, 6414AS, 6414TS, 6414VS, 6418AS, 6418TS, 6418S Tower RAID Enclosures. This is a replacement Drive Tray designed specifically for HighPoint RocketStor Tower RAID Enclosures.</p>
	<p><b>EXT-MS-1MMS</b> - The Ext-MS-1MMS is a high-speed cable that supports a data bandwidth up to 4x 6Gb/s between the RocketStor 6418TS RAID controller installed in the host system, and the 8-Bay Enclosure via SFF-8088 ports. Each cable can connect up to 4x Hard Drives or SSDs.</p> <p>Suggested Uses:</p> <ol style="list-style-type: none"> <li>1) Spare cable</li> <li>2) Replacement</li> </ol>
	<p><b>RocketStor 6414S</b> - The RocketStor 6414S is a 4-Bay JBOD enclosure designed for use with the RocketStor 6418TS to house up to 4x 2.5" or 3.5" Hard Drives or SSDs.</p> <p>Suggested Uses:</p> <ol style="list-style-type: none"> <li>1) Replacement</li> <li>2) Additional Storage or Back up Unit</li> </ol>
	<p><b>RocketStor 6418S</b> - The RocketStor 6418S is an 8-Bay JBOD enclosure designed for use with the RocketStor 6418TS to house up to 8x 2.5" or 3.5" Hard Drives or SSDs.</p> <p>Suggested Uses:</p> <ol style="list-style-type: none"> <li>1) Replacement</li> <li>2) Additional Storage or Back up Unit</li> </ol>

HighPoint Headquarters  
 Phone 1-408-942-5800  
 Fax 1-408-942-5801  
 E-mail sales@highpoint-tech.com  
 Website www.highpoint-tech.com  
 Address 1161 Cadillac Ct. Milpitas CA, 95035

HighPoint Taiwan  
 Phone + 886-2-2218-3435  
 Fax + 886-2-2218-3436  
 E-mail sales@highpoint-tech.com  
 Website www.highpoint-tech.com  
 Address SF., No.3, Swei Lane, Jhongjheng Rd., Sindian District, New Taipei City 23148, Taiwan (R.O. .C. .)

HighPoint China  
 Phone + 86-10-6213-0920  
 Fax + 86-10-6897-5074  
 E-mail sales@highpoint-tech.com  
 Website www.highpoint-tech.cn  
 Address 4th Floor Kehaifulin Building, NO. 12 Zhong Guan Cun South Rd, Aidian District Beijing China 100081